

## Ordering Information

HDV600 models are available from authorized Extech distributors. To learn more, or to find a distributor, please visit [www.extech.com/hdv600](http://www.extech.com/hdv600).

### Video Inspection Camera Kits

|         |  |
|---------|--|
| HDV610  | High definition videoscope (5.5mm diameter camera with macro lens/1m flexible cable)                       |
| HDV620  | High definition videoscope (5.8mm diameter camera with macro lens/1m semi-rigid cable)                     |
| HDV640  | High definition articulating videoscope (6mm diameter camera with macro lens/1m semi-rigid cable)          |
| HDV640W | High definition wireless articulating videoscope (6mm diameter camera with macro lens/1m semi-rigid cable) |

### Video Inspection Display Unit (order probes and handsets separately)

|        |   |
|--------|---|
| HDV600 | High definition videoscope display unit, monitor, hard case and related accessories only) |
|--------|---|

### Handsets & Accessories

|          |  |
|----------|--|
| HDV-TX1  | 6mm articulating handset with probe with macro lens (1m semi-rigid cable)          |
| HDV-WTX1 | 6mm wireless articulating handset with probe with macro lens (1m semi-rigid cable) |
| HDV-TX2  | 6mm articulating handset with probe with macro lens (2m semi-rigid cable)          |
| HDV-WTX2 | 6mm wireless articulating handset with probe with macro lens (2m semi-rigid cable) |
| HDV-WTX  | Wireless handset (accepts all optional probes below)                               |
| HDV-PC   | Spare patch cable for HDV600 series handsets                                       |

### Optional Probes

|               |  |
|---------------|--|
| HDV-4CAM-1FM  | 4mm videoscope probe with macro lens (1m flexible cable)                   |
| HDV-4CAM-5FM  | 4mm videoscope probe with macro lens (5m flexible cable)                   |
| HDV-5CAM-1FM  | 5.5mm videoscope probe with macro lens (1m flexible cable)                 |
| HDV-5CAM-3F   | 5.5mm videoscope probe with long depth of field lens (3m flexible cable)   |
| HDV-5CAM-3FM  | 5.5mm videoscope probe with macro lens (3m flexible cable)                 |
| HDV-5CAM-30FM | 5.5mm videoscope probe with macro lens (30m flexible cable)                |
| HDV-5CAM-10F  | 5.5mm videoscope probe with long depth of field lens (10m flexible cable)  |
| HDV-5CAM-1R   | 5.8mm videoscope probe with long depth of field lens (1m semi-rigid cable) |
| HDV-5CAM-1RM  | 5.8mm videoscope probe with macro lens (1m semi-rigid cable)               |
| HDV-5CAM-3R   | 5.8mm videoscope probe with long depth of field lens (3m semi-rigid cable) |
| HDV-5CAM-3RM  | 5.8mm videoscope probe with macro lens (3m semi-rigid cable)               |
| HDV-25CAM-10G | 25mm videoscope probe with long depth of field lens (10m fiberglass cable) |
| HDV-25CAM-30G | 25mm videoscope probe with long depth of field lens (30m fiberglass cable) |

## About Extech Instruments

Extech Instruments is recognized as the source for the best handheld test and measurement tools worldwide. Founded in 1971, Extech is known for its depth and breadth of innovative inspection tools, testers, and meters suited for electrical, HVAC, building/restoration, and other industries. Extech also offers a host of environmental testers for measurement of sound, light, humidity and other parameters. All Extech tools are distributed worldwide through leading representatives, distributors and OEMs. The company is headquartered in the Northeastern United States and is ISO 9001:2008 certified. Extech is a wholly owned subsidiary of FLIR Systems, Inc.

## High-Definition VideoScope

### HDV600 Series



Home Inspection • Industrial Manufacturing • Automotive/Aerospace • HVAC/Environmental • Safety/Security





# HIGH DEFINITION VIDEOSCOPIES

## HDV600 Series

# Inspect More. See More. Find More.

### Introducing the HDV600 Series from Extech

From the makers of the best test and measurement instruments comes a new generation of high-definition inspection cameras. Introducing the HDV600 videoscopes, designed for ruggedness, upgradeable versatility, and high-definition clarity. HDV600 videoscopes feature a large color display, SD memory, LED illuminated handset probes, and glove-friendly controller handsets.

Inspect more, see more, and find more with the Extech HDV600 VideoScope Series.

### Ruggedly Reliable by Design



Extech's durable display unit is built for tough job sites, ready to handle the unexpected drop off a ladder, or torrential

rains at an outdoor facility. The HDV600 main display unit features a large 5.7" (145mm) LCD monitor that is easy to view in bright outdoor sites, cramped and poorly lit industrial spaces, or aircraft maintenance facilities.



- **Waterproof display unit**
- **Drop-proof to 2 meters (6.5')**
- **Ergonomic, adjustable grips**
- **Left/right hand controls**



### Remarkable Images and Video

Capture clear images and video you can use to quickly find and document problems. Select optics that are ideal for your job requirements. Record nearly 15,000 images or up to 4 hours of video on an easy to transfer SD memory card. Plus, audio annotations can be added to video clips, helping to minimize note-taking.

### Optics for Every Application

Learn how different optical camera tips available with the HDV600 videoscopes satisfy varying job requirements. Decide if one or both is right for your job knowing the HDV600 Series offers different optics mated to a range of probes.

**Macro Lens**  
0.59" - 2.36"  
(20 - 60 mm)

**Long Focus Lens**  
2.36" - ∞  
(60 mm - ∞)

**Macro (Short Focal Length) Lenses** permit you to examine features and attributes that are up-close to the optical camera tip as illustrated above. For detail-intensive applications, such as turbine blade or boiler tube inspections, where up-close viewing is essential, select a macro tip with a diameter that is compatible with the width of access points or orifices available.

**Long Focus Lenses** permit you to see further in confined areas. These are ideal for viewing concealed areas or large, otherwise inaccessible locations where areas needing inspection may not be immediately adjacent to the optical tip.



- **640 x 480 pixel resolution**
- **Macro & long focal length optics available**
- **Easy-to-transfer SD card**
- **15,000 JPEG images**
- **Up to 4 hours AVI video**
- **Audio annotation**

**HDV600 is optimized for a wide range of industries**

- **Industrial Processing & Manufacturing**
- **Heavy Equipment**
- **HVAC/Boilers**
- **Aerospace**
- **Government & Security**
- **Insurance**

- **Forensic Investigations**
- **Aviation AOG and FBO**
- **Power Generation**
- **Building Inspection & Commissioning**
- **PetroChem/Refineries**
- **Infrastructure**



All HDV600 optical camera tips are designed with bright, integrated LED lighting, useful for illuminating dark locations or concealed components.



Articulated 6mm scopes dramatically expand viewing capabilities with 320° (160° left, 160° right) articulation control.

Large, glove-friendly, articulation control knob with adjustable resistance enables inspections in any environment.

## HDV600 Handset Controllers: More Convenience. More Control

Access impressive versatility with a range of options designed to ensure the right scope for the job, without sacrificing upgradeability. In addition to probes which connect directly to the main display unit, handset-mounted probes make it easier than ever to inspect difficult-to-access areas.

Options include:

- Scope probes connected to videoscope main unit
- Wired handset scope probes (also available separately)
- Wireless handset scope probes for inspections up to 10m away (also available separately)
- Articulating handset probes (wired and wireless models available)
- Semi-rigid, flexible, and long-length scopes available
- Scope lengths range from 1m to 30m with custom lengths available
- 4-25mm diameter optics including macro and long focal length options



## Display Unit-Mounted Scope Probes



**HDV610** VideoScope with 5.5mm diameter flexible probe (1m length)



**HDV620** VideoScope with 5.8mm diameter semi-rigid probe (1m length)

## Handset-Mounted Scope Probes



**HDV640** VideoScope, wired handset & 6mm diameter semi-rigid articulated (320°) probe



**HDV640W** VideoScope, wireless handset & 6mm diameter semi-rigid articulated (320°) probe



**HDV-TX1, HDV-TX2** Wired handset with 6mm diameter semi-rigid articulated (320°) probe (1m, 2m versions)



**HDV-WTX** Universal wireless handset, accepts several scopes of varying diameters, lengths, and flexibility



# VideoScope Selector Guide

Use this guide to evaluate all available configuration options

| Features to look for   | Complete Videoscope Kits |        |        |          | Optional Articulated Handsets with Probe |   |          |   | Optional Universal Handset w/o Probe | Optional Probes |               |               |               |              |               |               |               |              |               |              |               |                |
|--|--------------------------|--------|--------|----------|--|---|----------|---|--------------------------------------|-----------------|---------------|---------------|---------------|--------------|---------------|---------------|---------------|--------------|---------------|--------------|---------------|----------------|
|  | HDV610                   | HDV620 | HDV640 | HD-V640W | Wired                                    |   | Wireless |   |                                      | Wireless        | HDV-4CAM -1FM | HDV-4CAM -5FM | HDV-5CAM -1FM | HDV-4CAM -3F | HDV-5CAM -3FM | HDV-5CAM-30FM | HDV-5CAM -10F | HDV-5CAM -1R | HDV-5CAM -1RM | HDV-5CAM -3R | HDV-5CAM -3RM | HDV-25CAM -10G |
| Videoscope with probe mounted to main display unit   | ●                        | ●      | ▲      | ▲        | —  | — | —        | — | —                                    |                 |               |               |               |              |               |               |               |              |               |              |               |                |
| Videoscope with probe mounted to a remote handset  | ▲                        | ▲      | ●      | ●        | ■  | ■ | ■        | ■ | ■                                    |                 |               |               |               |              |               |               |               |              |               |              |               |                |
| Videoscope with probe mounted to a wireless remote handset (10m range)                                   | ▲                        | ▲      | ▲      | ●        | —  | — | ■        | ■ | ■                                    |                 |               |               |               |              |               |               |               |              |               |              |               |                |
| Probe with 320° articulating control for expanded viewing angles   | ▲                        | ▲      | ●      | ●        | ■  | ■ | ■        | ■ | ■                                    |                 |               |               |               |              |               |               |               |              |               |              |               |                |
| Probe length (meters)  | 1                        | 1      | 1      | 1        | 1  | 2 | 1        | 2 | ■                                    | 1               | 5             | 1             | 3             | 3            | 30            | 10            | 1             | 1            | 3             | 3            | 10            | 30             |
| ∅ Lens diameter (mm)   | 5.5                      | 5.8    | 6      | 6        | 6  | 6 | 6        | 6 | ■                                    | 4               | 4             | 5.5           | 5.5           | 5.5          | 5.5           | 5.5           | 5.8           | 5.8          | 5.8           | 5.8          | 25            | 25             |
| Macro/short focal length (M) lens for up-close detail or long focal length (L) to inspect larger voids   | M                        | M      | M      | M        | M  | M | M        | M | ■ M, L                               | M               | M             | M             | L             | M            | M             | L             | L             | M            | L             | M            | L             | L              |
| Probe flexibility: semi-rigid (R), flexible (F), or fiberglass (G) for spooled, long-length applications | F                        | R      | R      | R        | R  | R | R        | R | ■ R, F, G                            | F               | F             | F             | F             | F            | F             | F             | R             | R            | R             | R            | G             | G              |

Expand your HDV600's versatility with additional non-articulated probes that connect to your display unit as well as wired/wireless handsets (non-articulated handsets only).

**KEY**

- Standard feature
- ▲ This display unit supports this feature using optional accessories
- This optional accessory can be used to support or expand this feature.
- M Macro Lens
- L Long Focal Length Lens
- R Semi-rigid Probe
- F Flexible Probe
- G Fiberglass Probe

## Upgradeable Versatility by Design

The HDV600 series is designed with capabilities and accessories to give you a rolling start while still permitting you to expand functionality as your needs change.



### Job-Ready

HDV600 VideoScope kits include:

- VideoScope display unit
- Wired or wireless handset
- 1 m flexible or semi-rigid probe with macro optics
- 1GB SD memory card
- 3.7V rechargeable Li-Polymer battery
- Probe accessories: magnet, 45° mirror, and anti-snag tip
- Patch cable
- AC adaptor
- USB and AV cables
- Hard carrying case

### Customizable

You may also configure customized solutions by starting with an HDV600 display unit (no probe included) and selecting optional probes and/or handsets listed above.



### Expandable

Are your inspections changing? Is your business growing? The HDV600 series grows with you.

#### You can order:

- Wired and wireless articulated handsets
- Universal wireless handsets
- Probes with different lengths, optics diameters, or flexibility

